

Single part, non shrink, cementitious, crack filler for plaster, masonry and concrete

Uses

Renderoc CF is used for filling cracks on plaster, masonry and concrete substrates.

Advantages

- **Single component** - Easy to use
- **Versatile** - Can be used for cracks in exposed conditions on plaster, masonry or concrete upto 20mm width
- **Non sagging** - Can be used for horizontal, vertical and overhead applications
- **Good adhesion** - Effective bonding with substrate
- **Non Shrink** - Shrinkage cracking eliminated
- **Hydrophobic** - enhanced waterproofing property

Description

Renderoc CF is a crack sealing/filling cementitious material in powder form. It is easy to apply and can be finished or smoothed off with a putty blade or a damp sponge. It sets quickly on application and can be over coated with common paints / coatings.

Properties

Colour	White / grey
Pot life	30 min
Compressive strength (ASTMC109)	18 N/mm ² in 7days and 20 N/mm ² in 28 days
Fresh wet density	1.95 g/cc
W/p Ratio	0.23 by weight
Mix proportions by volume	1 part water: 3 parts of powder
Minimum application temperature	10°C

Application instructions

Surface Preparation

The cracks to be sealed shall be saw cut or chiselled to form a 'V' groove of approximately of 6mm x 6mm. The grooves shall be cleaned to remove all the loose particles, dust, etc.

The groove shall be sprinkled with clean water before applying the sealing mortar.

Mixing

Renderoc CF shall be mixed with water adopting w/p ratio 0.23 by weight or a mix porportion of 1 part of water to 3.0 parts of Renderoc CF, by volume. Thorough mixing shall be carried out till a smooth, homogenous paste is obtained.

Application

The mixed paste is filled into the groove by gloved hand and the surface finished using a trowel. This is continued till the full length of crack is sealed.

Curing

Curing is necessary only when groove size exceeds 6mm width or in areas exposed to UV.

Cleaning

Tools may be cleaned with clean water as Renderoc CF is a cement based product

Limitations

Renderoc CF crack sealer/filler cannot be used for moving cracks and for crack width greater than 20mm

Renderoc CF

Estimating

Packaging

Renderoc CF is supplied in 1, 5 & 25 kg packs.

Coverage

About 30 RM for a V groove crack of 6mm x 6mm for 1 kg. pack. The actual coverage may vary depending on the substrate conditions

Storage

Shelf life

Renderoc CF has a shelf life of 12 months in original unopened packs if stored in unopened conditions below 35°C

Precautions

Health & Safety instructions

Renderoc CF has no health hazards in normal use. Gloves shall be worn while mixing and during application. Splashes of material to the eyes shall be washed off with clean water. In the event of prolonged irritation, medical advice shall be sought.

Fire

Renderoc CF is non flammable.

Additional information

Fosroc manufactures a wide range of products specifically designed for the repair and refurbishment of damaged reinforced concrete. These include hand placed and trowellable repair mortars, fluid micro concretes, chemical resistant epoxy mortars and a comprehensive package of protective coatings. In addition, a wide range of complimentary products are available. These include admixtures, joint sealants, waterproofing membranes, grouting, anchoring, and specialised flooring materials.

Separate datasheets are available on these products



Fosroc Chemicals (India) Pvt. Ltd.

Head Office

Embassy Point, No. 150,
2nd Floor, Infantry Road,
Bangalore 560 001,
Karnataka

Important note :

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

telephone

+91 80-42521900

fax

+91 80-22281510

e-mail

enquiry.india@fosroc.com

Regional Offices

Chennai

Hills Centre, Old No 5,
New No 9, 3rd Cross Street,
Jeth Nagar, Raja Annamalaipuram,
Chennai 600 028.
Ph: 9500064795

Mumbai

MBC Park, 12th floor, Office No.12B,
'D' Block, Near G Corp/Hyper City
Kasarwadawali, Ghodbunder Road,
Thane (West) 400 615
Ph: +91 22 6229 6800

Noida

Unit No. 601, Highway Tower-II
A-13/2, 6th Floor, Sector- 62
Gautam Buddha Nagar,
Noida 201 309, Uttar Pradesh
Ph: +91 120 6121900
Fax: 0120-4270622

Kolkata

304, Jodhpur Park
Kolkata 700 068
Ph: +91 33-65343188
Fax: 033-2499-0278